



WWW.antislip-uk.co.uk

TECHNICAL DATA SHEET

ANTISLIP STEP 2

Single Component Compound For Increasing Coefficient of Friction

Antislip Step 2 is a fast acting compound designed to penetrate into the surface pores of all natural stones and glazed materials to increase the coefficient of friction or SRV in wet conditions

Antislip Step 2 is specially formulated for application to Ceramic Tiles, Quarry Tiles, Marble, Granite, Porcelain and Terrazzo and most stone masonry surfaces.

Antislip Step 2 can only be applied in conjunction with **Antislip Step 1/3**

Antislip Step 2 is not an acid etching system and therefore can safely be used on highly glazed tiles and natural stones. (Always undertake a small trial area)

Before proceeding please read carefully the following information to ensure correct application procedures are fully understood.

Mixing

Supplied as a single component material ready for use

Mixing Ratios: Not applicable

Application

Antislip Step 2 should be poured into a plastic container taking care not to splash the material around. The material should be applied directly on to the floor using a low- pressure pump spray and absorbent application pad (see **Antislip** application instructions. A thin and even coat of **Antislip Step 2** should be applied over the entire floor area at the recommended coverage rate The floor should be kept wet with **Antislip Step 2** and **not allowed to dry out.** **Antislip Step 2** should be kept on the floor until an increase in grip is noticed. This will take between 7 to 20 minutes depending on the substrate. (See **Antislip** application instructions for substrate- times) Once an adequate increase in grip has occurred **Antislip Step 1/3 mixed 4:1** with hot water should be applied directly on top of the wet **Antislip Step 2** and this thoroughly scrubbed in with a deck brush or rotary scrubber. The entire area should then be thoroughly swilled down and all standing water removed with either a squeegee or wet vacuum. The waste materials can be disposed of down a normal foul water drain.



WWW.antislip-uk.co.uk

PHYSICAL CONSTANTS

Mixing Ratio	Supplied ready for use
Coverage Rates	1 litre will treat 10M ² – 12 M ² applied by spray
Appearance	Orange liquid
Shelf Life	Use within 12 months of purchase Store in original sealed containers at temperatures between 5 Deg C (40 Deg F) and 30 Deg C (86 Deg F) PROTECT FROM FROST

HEALTH AND SAFETY

As long as normal practice is observed **Antislip Step 2** can safely be used.

PVC or rubber gloves should be worn.

Protective goggles and overalls should be worn if splashes are likely to occur.

A fully detailed **Material Safety Data Sheet** is either included with the material or is available on request.

PACKAGING

Supplied in 25litre 10 litre and 5 litre units. This product is only supplied in conjunction with **Antislip Step 2**

The information provided by this Product Data Sheet is intended as a general guide only and should not be used for specification purposes. The information is given in good faith but assuming no responsibility for the use made of the product or this information because this is outside the control of the company. Users should determine the suitability of the product for their own particular purposes by undertaking their own tests.



Antislip Step is distributed in the UK by

Surefoot Systems UK Ltd
164 Marsh Lane
Shepley
Huddersfield HD8 8AX
Tel/Fax: +44(0) 1484608001
E Mail: enquiries@surefoot-uk.co.uk



WWW.antislip-uk.co.uk

TECHNICAL DATA SHEET

ANTISLIP STEP 1/3

Single Component Citrus Concentrate

Antislip Step 1/3 is a multipurpose compound used for cleaning and priming the substrate and as a locking/neutralising agent for **Antislip Step 2**.

Antislip Step 1/3 must always be used to clean and prepare the surface prior to the application of **Antislip Step 2**.

Antislip Step 1/3 must always be used in the final process to neutralise and lock in the **Antislip Step 2**.

Antislip Step 1/3 is Phosphate free and environmentally safe to use.

Before proceeding please read carefully the following information to ensure correct application procedures are fully understood.

Mixing

Supplied as a single component material that only requires diluting with hot water prior to use.

Mixing Ratios: For surface cleaning and priming prior to the application of **Antislip Step 2** the mixing ratio should always be 1 litre to 4 litres of hot Water or 4:1.

Antislip Step 4 Cleaner Maintainer can be used on floors where there is an excessive build up of grease or contamination prior to the application of **Antislip Step 1/3**. (See Technical Data Sheet **Antislip Step 4**)

For neutralising and locking the **Antislip Step 2** into the surface the mixing ration should always be 1litre to 4 litres of hot water or 4:1

Application

Apply **Antislip Step 1/3** generously to the floor and activate with a deck brush or rotary power scrubber. Allow the solution to work for at least 5 minutes then thoroughly remove from the surface with hot water. **It is essential that all traces of the Antislip Step 1/3 are removed from the surface and from grouting. If in doubt apply more clean hot water.** The surface should then be totally dried using a wet vacuum or clean mop.



WWW.antislip-uk.co.uk

PHYSICAL CONSTANTS

Mixing Ratio	For cleaning and priming (Step 1) One part to 4 parts hot water. This ratio should always be used. For neutralising and locking the surface (Step 3) One part to 4 parts hot water. This ratio should always be used.
Coverage Rates	1 litre mixed with 4 litres hot water approx 25 to 30 M2
Appearance	Golden/Green liquid
Shelf Life	Use within 12 months of purchase Store in original sealed containers at temperatures between 5 Deg C (40 Deg F) and 30 Deg C (86 Deg F) PROTECT FROM FROST

HEALTH AND SAFETY

As long as normal practice is observed [Antislip Step 1/3](#) can safely be used.

PVC or rubber gloves should be worn.

Protective goggles should be worn if splashes are likely to occur.

A fully detailed **Material Safety Data Sheet** is either included with the material or is available on request.

PACKAGING

Supplied in 25litre 10 litre and 5 litre units. This material is only supplied in conjunction with [Antislip Step 2](#)

The information provided by this Product Data Sheet is intended as a general guide only and should not be used for specification purposes. The information is given in good faith but assuming no responsibility for the use made of the product or this information because this is outside the control of the company. Users should determine the suitability of the product for their own particular purposes by undertaking their own tests.



[Antislip](#) is distributed in the UK by:

Surefoot Systems UK Ltd
164 Marsh Lane
Shepley
Huddersfield HD8 8AX
Tel/Fax: +44(0) 1484608001
E Mail: enquiries@surefoot-uk.co.uk